



MODEL	XPR-10AC	XPR-10ACX
Lifting Capacity*	10,000 Lbs. / 4536 Kg.	10,000 Lbs. / 4536 Kg.
*Max Capacity / Front Axle	5,000 Lbs. / 2268 Kg.	5,000 Lbs. / 2268 Kg.
*Max Capacity / Rear Axle	5,000 Lbs. / 2268 Kg.	5,000 Lbs. / 2268 Kg.
A - Height Overall: (*)	145" / 3683 mm.	145" / 3683 mm.
B - Width Overall (Outside of Base Plate):	132" / 3353 mm.	145" / 3683 mm.
C - Width (Outside of Columns):	126" / 3200 mm.	139" / 3531 mm.
D - Floor To Overhead Switch: (*)	141" / 3581 mm.	141" / 3581 mm.
E - Inside Columns:	99" / 2515 mm.	112" / 2845 mm.
F - Reach (Front Arm Min.):	21" / 533 mm.	25" / 635 mm.
G - Reach (Front Arm Max.):	41" / 1041 mm.	46" / 1168 mm.
H - Reach (Rear Arm Min.):	42" / 1067 mm.	42" / 1067 mm.
I - Reach (Rear Arm Max.):	60" / 1524 mm.	60" / 1524 mm.
J - Min. Pad Height:	4" / 102 mm.	4" / 102 mm.
K - Rise:	69" / 1753 mm.	69" / 1753 mm.
L - Max Lift Height (Pad Only):	73" / 1854 mm.	73" / 1854 mm.
M - Max Lift Height (6" Adapter):	79" / 2007 mm.	79" / 2007 mm.
N - Drive-Thru Clearance:	89" / 22261 mm.	102" / 2591 mm.
Motor (**)	220 VAC / 60 Hz. 1Ph.	220 VAC / 60 Hz. 1Ph.
Time of full Rise:	45 Seconds	45 Seconds
Max Load Per Arm:	2,500 Lbs. / 1134 Kg.	2,500 Lbs. / 1134 Kg.
* An optional bolt-on top extension for columns raises the overhead bar an additional 24". Must be ordered from factory at time of order.		
** Special Voltages Available Upon Request.		
The design, material and specifications are subject to change without notice.		